

SUSPENSION

EVACUATION AND FILLING DEVICE FOR SHOCK ABSORBERS EBS 100

ARTICLE NO. 400.505.100



**THE
PROFESSIONAL
FOR SHOCK
ABSORBER
SERVICE.**



The EBS 100 is the only device of its kind in the world. It can be used to perform service on the most advanced suspension systems. The ability to flexibly adjust the pressure is particularly suitable for flushing the kinetic suspensions of all current and future vehicles.

Due to the simple operation and the robust construction made of steel, it is well equipped to withstand the tough daily workshop routine. High-quality handles, smooth-running heavy-duty rollers with large radii and an impact-resistant powder coating make the EBS100 a device for many years of use.

FUNCTIONS:

- Independent venting of the internal device pipelines
- Inspection through integrated sight glass
- Bubble free filling of hydraulic systems with adjustable pressure between 4 and 40 bar
- Bringing hydraulic systems to ambient pressure in a controlled manner through drain hose with ball valve
- Connection to waste oil tank via oil drain hose
- Blowing out hydraulic systems with compressed air
- Disposal of used oil in canister
- Generation of vacuum up to an absolute pressure of 0.002 bar

All functions can be realized by turning two levers. Once connected to the vehicle it is not necessary to reconnect hoses during this process.



SUSPENSION

TECHNICAL DATA	EVACUATION AND FILLING DEVICE FOR SHOCK ABSORBERS EBS 100
Article no.	400.505.100
Dimensions	607 x 690 x 1.002 mm
Mains voltage	230 V/50 Hz
Max. working pressure	40 bar
Power cord length	3 m
Old oil container volume	10 l
New oil container volume	8 l

DELIVERY INCLUDES

- Old oil container 10 liter

